

Capnocheck® Sleep Capnograph/Oximeter



The BCI® Capnocheck® Sleep Capnograph/Oximeter is specially designed for sleep screenings and lab-based sleep studies. Its 4-channel analog output capability lets you select ETCO₂ numeric value, ETCO₂ waveform, inspired CO₂, respiratory rate, heart rate, as well as SpO₂ numeric and waveform displays. The BCI® Capnocheck® Sleep interfaces easily with most polysomnograph equipment for enhanced detection of respiratory depression during sleep.

For more information visit smiths-medical.com/bci.

PATIENT MONITORING



Capnocheck® Sleep Capnograph/Oximeter

- Quiet System minimizes monitor noise.
- Patented technology reliably measures SpO₂.
- Breath-by-breath CO₂ detection allows rapid response to patient changes.
- Disappearing display and no audible alarms or pulse tones in sleep mode minimize patient distraction.
- 4-channel analog output capability offers versatile room and sleep lab set-up.
- Perform non-lab or preliminary sleep studies via PC analysis software.
- Incorporates economical sidestream technology.

Technical Specifications

DISPLAYS, INDICATORS AND KEYS

- **Display**
Vacuum fluorescent
- **Indicators**
Alarm, charge, silenced
- **Displayed Trends**
Graphical display, user selectable sample rate, user selectable trend up to 16 hr display at 12 sec sample rate up to 10 hr display at 4 sec sample rate
- **Displayed**
Selectable CO₂ or CO₂/plethysmogram
- **Waveforms**
Waveform

ALARMS

- **Physiological**
Adjustable volume user-selectable high and low limits for all displayed parameters
Screen indicators for each parameter
- **System**
Adjustable volume
- **Silence**
Temporary 2 min or OFF LED indicator

FLOW RATE

150 ml/min, ± 20

CO₂

- **Measurement**
Non-dispersive IR absorption
- **Measurement Range**
0-10% CO₂ STPD
(standard temperature and pressure dry)
- **Units**
User-selectable: mmHg, Vol. %, kPa
- **Display Range**
0-100 mmHg or 0-10.0% CO₂ or 0-13.3 kPa
- **Accuracy**
±2 mmHg; ±0.3%; ±0.3 kPa, or 4% of reading, whichever is greater (0-10% CO₂)
- **Resolution**
1 mmHg; 0.1%; 0.1 kPa
- **Calibration**
2 point cal
- **N₂O Compensation**
User-selectable 40% (default=OFF)

- **Rise Time**
360 ms (average)
- **Averaging**
4-breath average, or breath-to-breath selectable

RESPIRATION RATE

- **Range**
0-150 bpm
- **Averaging**
4 breath average
- **Accuracy**
±1 bpm

SPO₂

- **Range**
0 to 100% SpO₂ (functional)
- **Accuracy**
±2% at 70-100%; <70% unspecified
- **Averaging**
2, 4, 8, or 16-beat averaging (default: 2)

PULSE RATE

- **Range**
30-254 bpm
- **Accuracy**
Greater of ±2 bpm or ±2%
- **Averaging**
8 seconds
- **Pulse Tone**
Pitch corresponds SpO₂ value
Volume adjustable or OFF

POWER REQUIREMENTS

105-125 VAC, 60 Hz
90-110 VAC, 50 Hz (optional)
208-252 VAC, 50/60 Hz (optional)

BATTERY LIFE

Nickel cadmium battery, 6 VDC, internal rechargeable, not user replaceable, fully-charged continuous life of approximately 2 hours, maximum full charge time 4 hours.

ANALOG OUTPUT

- **Any four**
CO₂ waveform, plethysmogram, end tidal CO₂, respiration rate, inspired CO₂, % SpO₂, pulse rate, 0 V or 1 V cal signal

- **Range**
0-1 VDC full scale

SERIAL OUTPUT

- **RS232C**
Tabular trends, patient data
- **Sleep Study**
10 hrs at 4 sec, 31 hrs at 12 sec

DIMENSIONS

3.5" H x 10.0" W x 5.5" D
(8.9 cm H x 25.4 cm W x 13.9 cm D)

WEIGHT

- **Base Unit**
4.8 lbs. (2.2 kg)

ENVIRONMENTAL

- **Operating Temperature**
32°F to 122°F (0°C to 50°C)
- **Storage Temperature**
-40°F to 158°F (-40°C to 70°C)
- **Relative Humidity** (non-condensing)
10-95% (storage)
15-95% (operating)

STANDARDS

EN60601-1, (IEC 60601-1),
EN60601-1-2, EN60601-1-1,

REGULATORY COMPLIANCE

ISO 9001/ISO 13485

CATALOG NUMBER

- **9004-050**
Capnocheck® Sleep Capnograph
- **9004-051**
Capnocheck® Sleep Capnograph/Oximeter

Information subject to change without notice. Please read the Instructions for Use supplied with the product for detailed instructions, warnings and cautions.

Q-Line for U.S.A. customers: call 1-800-348-1842 for clinical application information.

For more information, please call Smiths Medical PM, Inc., at 262-542-3100 or 800-558-2345, or your Smiths Medical distributor.

Smiths Medical PM, Inc.

Patient Monitoring and Ventilation

N7W22025 Johnson Drive, Waukesha, Wisconsin 53186 USA

Phone: 262-542-3100 Fax: 262-542-0718 Toll-Free: 800-558-2345

www.smiths-medical.com/bci

Smiths Medical, part of the global technology business Smiths Group

BCI, Capnocheck and the Smiths Medical design mark are trademarks of the Smiths Medical family of companies. The symbol ® indicates the trademark is registered in the U.S. Patent and Trademark Office and certain other countries. All other names and marks mentioned are the trade names, trademarks or service marks of their respective owners. © 2008 Smiths Medical family of companies. All rights reserved. BCI 9004-051 Rev.03 05/08

smiths medical